

Sampling and Reconstruction

The sampling and reconstruction process

- Real world: continuous
- Digital world: discrete

Basic signal processing

- Fourier transforms
- The convolution theorem
- The sampling theorem

Aliasing and antialiasing

- Uniform supersampling
- Nonuniform supersampling

Imagers = Signal Sampling

All imagers convert a continuous image to a discrete sampled image by integrating over the active "area" of a sensor.

$$R = \int_t \int_w \int_A L(x, \mathbf{w}, t) P(x) S(t) \cos \mathbf{q} \, dA \, d\mathbf{w} \, dt$$

Examples:

- Retina: photoreceptors
- CCD array
- Vidicon: phosphors


Virtual "computer graphics" cameras do not integrate, instead they simply sample ...

Displays = Signal Reconstruction

All physical displays recreate a continuous image from a discrete sampled image by using a finite sized source of light for each pixel.

Examples:

- DAC's: sample and hold
- Cathode ray tube: phosphor spot and grid



CS348B Lecture 7

Pat Hanrahan, Spring 2000

Sampling in Computer Graphics

Artifacts due to sampling - Aliasing

- Jaggies
- Moire
- Flickering small objects
- Sparkling highlights
- Temporal strobing



Preventing these artifacts - Antialiasing

CS348B Lecture 7

Pat Hanrahan, Spring 2000

Jaggies

Retort sequence by Don Mitchell



Staircase pattern or jaggies

CS348B Lecture 7

Pat Hanrahan, Spring 2000

Spectral Analysis / Fourier Transforms

Spectral representation treats the function as a weighted sum of sines and cosines

Each function has two representations

- Spatial (time) domain - normal representation
- Frequency domain - spectral representation

The *Fourier transform* converts between the spatial and frequency domain


$$\begin{array}{ccc} \boxed{\text{Spatial Domain}} & \begin{array}{c} \Rightarrow F(\mathbf{w}) = \int_{-\infty}^{\infty} f(x) e^{-i\mathbf{w}x} dx \\ \Leftarrow f(x) = \frac{1}{2\mathbf{p}} \int_{-\infty}^{\infty} F(\mathbf{w}) e^{i\mathbf{w}x} d\mathbf{w} \end{array} & \boxed{\text{Frequency Domain}} \end{array}$$

CS348B Lecture 7


Pat Hanrahan, Spring 2000

Spatial and Frequency Domain

Spatial Domain



Frequency Domain



CS348B Lecture 7

Pat Hanrahan, Spring 2000

Convolution

Definition

$$h(x) = f \otimes g = \int f(x')g(x-x')dx'$$

Convolution Theorem: Multiplication in the frequency domain is equivalent to convolution in the space domain.

$$f \otimes g \leftrightarrow F \times G$$


Symmetric Theorem: Multiplication in the space domain is equivalent to convolution in the frequency domain.

$$f \times g \leftrightarrow F \otimes G$$

CS348B Lecture 7

Pat Hanrahan, Spring 2000

Sampling: Spatial Domain




$$\text{III}(x) = \sum_{n=-\infty}^{n=\infty} d(x - nT) \quad f_s = \frac{1}{T} \quad w_s = 2\pi f_s = \frac{2\pi}{T}$$

CS348B Lecture 7

Pat Hanrahan, Spring 2000

Sampling: Frequency Domain




$$\text{III}(w) = \sum_{n=-\infty}^{n=\infty} d(w - nw_s)$$

CS348B Lecture 7

Pat Hanrahan, Spring 2000

Reconstruction: Frequency Domain




$$\Pi(x) = \begin{cases} 1 & |x| \leq \frac{1}{2} \\ 0 & |x| > \frac{1}{2} \end{cases}$$

CS348B Lecture 7

Pat Hanrahan, Spring 2000

Reconstruction: Spatial Domain




$$\text{sinc } x = \frac{\sin \boldsymbol{px}}{\boldsymbol{px}}$$

CS348B Lecture 7

Pat Hanrahan, Spring 2000

Sampling and Reconstruction



CS348B Lecture 7

Pat Hanrahan, Spring 2000

Sampling Theorem

This result is known as the Sampling Theorem and is due to Claude Shannon who first discovered it in 1949


A signal can be reconstructed from its samples without loss of information, if the original signal has no frequencies above $1/2$ the sampling frequency

For a given bandlimited function, the rate at which it must be sampled is called the Nyquist Frequency

CS348B Lecture 7

Pat Hanrahan, Spring 2000


Undersampling: Aliasing



CS348B Lecture 7

Pat Hanrahan, Spring 2000

Sampling a "Zone Plate"



Zone plate: $\sin x^2 + y^2$

Sampled at 128x128
Reconstructed to 512x512

Left rings: part of signal
Right rings: prealiasing
Middle rings: postaliasing

CS348B Lecture 7

Pat Hanrahan, Spring 2000

Ideal Reconstruction

Ideally, use a perfect low-pass filter - the sinc function - to bandlimit the sampled signal and thus remove all copies of the spectra introduced by sampling

Unfortunately,

- The sinc has infinite extent and we must use simpler filters with finite extents. Physical processes in particular do not reconstruct with sincs
- The sinc may introduce ringing which are perceptually objectionable

Mitchell Cubic Filter

$$h(x) = \frac{1}{6} \begin{cases} (12 - 9B - 6C)x^3 + (-18 + 12B + 6C)x^2 + (6 - 2B) & |x| < 1 \\ (-B - 6C)x^3 + (6B + 30C)x^2 + (-12B - 48C)x + (8B + 24C) & 1 < |x| < 2 \\ 0 & \text{otherwise} \end{cases}$$


Properties:

$$\sum_{n=-\infty}^{\infty} h(x) = 1$$

B-spline : (1,0)

Catmull - Rom : (0,1/2)

From Mitchell and Netravali
Look at other figures in that paper



Aliasing and Antialiasing

If the scene contains frequencies greater than the Nyquist Frequency, then we have a aliasing problem

Results of aliasing:

- Jaggies
- Moire
- Flickering small objects
- Sparkling highlights
- Temporal strobing


Preventing aliasing or antialiasing:

1. Analytically prefilter the signal
2. Uniform supersampling and resample
3. Nonuniform or stochastic sampling

CS348B Lecture 7

Pat Hanrahan, Spring 2000

Antialiasing by Prefiltering



CS348B Lecture 7

Pat Hanrahan, Spring 2000

Antialiasing by Prefiltering

Ideally, low-pass with a perfect filter (a sinc function) to bandlimit the function to the Nyquist sampling rate.

Unfortunately, the sinc has infinite extent and we must use simpler filters (like a box filter, or area average).


Practically:

- Constant colored polygonal fragments doable
- Complex environments not doable

Uniform Supersampling


Increasing the sampling rate moves each copy of the spectra further apart, potentially reducing the overlap and thus aliasing

Resulting samples must be resampled (filtered) to image sampling rate



Samples

$$Pixel = \sum_s w_s \cdot Sample_s$$



Pixel

Point vs. Supersampled



Point


4x4 Supersampled

Checkerboard sequence by Tom Duff

CS348B Lecture 7

Pat Hanrahan, Spring 2000

Analytic vs. Supersampled




Exact Area

4x4 Supersampled

CS348B Lecture 7

Pat Hanrahan, Spring 2000

Distribution of Extrafoveal Cones



Monkey eye cone distribution



Fourier transform

Yellot theory

- Aliases replaced by noise
- Visual system less sensitive to high frequency noise

CS348B Lecture 7

Pat Hanrahan, Spring 2000

Non-uniform Sampling

Intuition

Uniform sampling

- The spectrum of uniformly spaced samples is also a set of uniformly spaced spikes
- Multiplying the signal by the sampling pattern corresponds to placing a copy of the spectrum at each spike (in freq. space)
- Aliases are coherent, and very noticeable



Non-uniform sampling

- Samples at non-uniform locations have a different spectrum; a single spike plus noise
- Sampling a signal in this way converts aliases into broadband noise
- Noise is incoherent, and much less objectionable


CS348B Lecture 7

Pat Hanrahan, Spring 2000

Jittered Sampling




Add uniform random jitter to each sample



CS348B Lecture 7

Pat Hanrahan, Spring 2000

Jittered vs. Uniform Supersampling



Jittered Sampling

4x4 Uniform

CS348B Lecture 7

Pat Hanrahan, Spring 2000

Analysis of Jitter

Non-uniform sampling

$$s(x) = \sum_{n=-\infty}^{\infty} \mathbf{d}(x - x_n)$$

$$x_n = nT + j_n$$


Jittered sampling

$$j_n \sim j(x)$$

$$j(x) = \begin{cases} 1 & |x| \leq 1/2 \\ 0 & |x| > 1/2 \end{cases}$$

$$J(\mathbf{w}) = \text{sinc } \mathbf{w}$$



$$\begin{aligned} S(\mathbf{w}) &= \frac{1}{T} \left[1 - |J(\mathbf{w})|^2 \right] + \frac{2\mathbf{p}}{T^2} |J(\mathbf{w})|^2 \sum_{n=-\infty}^{\infty} \mathbf{d}\left(\mathbf{w} - \frac{2\mathbf{p}n}{T}\right) \\ &= \frac{1}{T} \left[1 - \text{sinc}^2 \mathbf{w} \right] + \mathbf{d}(\mathbf{w}) \end{aligned}$$



CS348B Lecture 7

Pat Hanrahan, Spring 2000

Poisson Disk Sampling



Dart throwing algorithm

CS348B Lecture 7

Pat Hanrahan, Spring 2000

Filtering Nonuniform Samples

1. Reconstruction

$$P = \frac{\sum_s w(x_s, y_s) \cdot S(x_s, y_s)}{\sum_s w(x_s, y_s)}$$

Note: For jittered samples may approximate with filter coefficients at centers of each cell


2. Filtering further attenuates high frequency noise

3. Problematical if samples are clumpy

CS348B Lecture 7

Pat Hanrahan, Spring 2000

Tiling



CS348B Lecture 7

Pat Hanrahan, Spring 2000